

HKT750LJ-6



- Powerful ISUZU 6WG1 engine, large displacement, power take-off. Large breakout forces enable rapid and extraordinary work performance.
- Rapid boom lifting speed and swing speed. High-pressure hoses for hydraulic pipelines to avoid damage and leakage.
- Strengthened raw materials drive the reliable structure. Waterproofing and dustproofing connectors deliver high security level.

MODEL

HKT750LJ-6

Basic parameters

| | | |
|-----------------------|----------------|---------|
| Operating weight | kg | 72000 |
| Bucket capacity | m ³ | 3.3-4.3 |
| Bucket breakout force | kN | 341 |
| Swing speed | rpm | 7.1 |
| Gradeability | degree | 35 |
| Boom length | mm | 6650 |
| Arm length | mm | 2900 |
| Flow rate | L / min | 2*425 |

Engine

| | | |
|----------------------|-----|------------|
| Model | | ISUZU 6WG1 |
| Power | kW | 377 |
| Rated rotation speed | rpm | 1800 |
| Emission limit | | Tier 3 |

Working range

| | | |
|---------------------------------|----|-------|
| Maximum digging height | mm | 11910 |
| Maximum dumping height | mm | 8245 |
| Maximum digging depth | mm | 7725 |
| Maximum vertical digging depth | mm | 4455 |
| Digging depth @ 2.5m | mm | 7030 |
| Maximum digging reach | mm | 12995 |
| Maximum digging reach at ground | mm | 12670 |